



PB-735 HD DP

Industrial Line

Automatic punch and bind machine for books and calendars

A further step for the automation of double loop binding. A clever and flexible machine able to punch and bind in line up to 9/16". Using the best of Rilecart technology, compact and user friendly, this machine is the perfect solution when in need to replace semiautomatic machinery with no risk of an underutilized investment.



www.rilecart.it


 **RILECART**® S.r.l.
WIREBIND INTERNATIONAL




PB 735 HD DP

Industrial Line

Automatic punch and bind machine for books and calendars




Double-action punching tool.



Division system

BINDING SYSTEM



TECHNICAL SPECIFICATIONS

	400 V 3-phase 50/60 Hz + Neutral; Kw 7
	6 Atm - 30 mc/hour
	H 1100 x D 2000 x L 4500
	2100 Kg

HOW IT WORKS

Calendars and books have to be put on the machine already collected. Then, depending on the thickness of the product the machine can be used in three ways:

- 1) Thickness less than 4 mm.: the machine in this case works in line without anything else to do, simply have to pick up the product bound on the conveyor.
- 2) Thickness from 4 mm. to 8 mm.: it is necessary to use the separating blade and split the product in two booklets that will be punched separately by the double-action punching tool.
- 3) Thickness from 8 mm. to 11 mm.: more over the maximum punching limit of the machine. It is necessary to split the book in two parts and then it will be automatically reassembled and bound. The PB-735 HD DP can be connected to gathering machines.

FEATURES

- Uses wires on spools.
- Maximum binding size:
for products up to 4 mm. thickness: 350 x 500 mm.
for products over 4 mm. thickness: 350 x 300 mm.
- Minimum binding size: 100 x 100 mm.
- Maximum punching thickness per stroke: 8 mm.
(4 + 4 mm. depending on pitch, materials and width of the product).
- Standard binding diameters: 1/4"
(on request 5/16", 3/8", 7/16", 1/2" and 9/16").
- Standard pitch 3:1" (on request 4:1" or 2:1").
- Speed variable 500 to 2300 pieces/hour depending on size, thickness and quality of materials.
- Can be programmed for continuous binding, two pieces with hanger or "skip-binding".
- Central automatic lubrication.


OPTIONALS

- Automatic device for hangers from 100 mm. to 200 mm.
- Option for automatic hanger feeder with hanger former.

	 Ø inch	 Ø mm	 mm	 axb mm	 Ø mm	 a mm
4:1"	1/4"	6,3	4,8	3,3x2,5	3	2
3:1"	1/4"	6,3	4,8	4x3	3,5	2
	5/16"	7,9	6,3	4x3,7	4	3
	3/8"	9,5	8			
	7/16"	11	9,5			
	1/2"	12,7	10,5	4x5	5	4
9/16"	14,3	11,5				

The Company reserves itself the right to modify the features of the products shown in this catalogue.

RILECART® S.r.l.
1870 WIREBIND INTERNATIONAL



RILECART - WIREBIND INTERNATIONAL
Headquarters and Factory:
Via Daniele Pesenti, n°1
24022 Alzano Lombardo - Bergamo
Tel. +39 035 515.900 - Fax +39 035 515.060
E-mail: info@rilecart.com - Internet: www.rilecart.com

